

Spoked Handwheels

Aluminum, Powder Coated Black

SPECIFICATION

Types

- Type **A**: Without handle
- Type **R**: With revolving handle

Bore codes

- Version **B**: Without keyway
- Version **K**: With keyway DIN 6885-1 P9

Wheel body

- Aluminum
- Hub machined
 - Rim
 - Turned on all sides
 - Radial and axial runout < 0,4
 - Powder coated
 - Black, textured finish

Revolving handle GN 798 (see page 577)

- Plastic, Polyamide (PA)
- Black, matte finish
 - Spindle steel
 - Zinc plated, blue passivated



INFORMATION

Spoked handwheels GN 324 are used for making adjustments or driving mechanisms.

Type R transmits fast adjustment movements via the revolving handle with decoupling. The revolving handle can be held firmly and safely while cranking.

For precise adjustment, the force applied by hand is transmitted via the rim.


Spoked handwheels can also be ordered with cross holes GN 110.

ACCESSORY

- GN 184 Countersunk Washers (for Axial Fastening) (see page 971)

TECHNICAL INFORMATION

- Keyway P9 DIN 6885-1 (see page A16)
- Cross holes GN 110 (see page A17)
- ISO-Fundamental Tolerances (see page A21)



* Complete with

- B** without keyway **K** with keyway

GN 324-A

Description	d ₁	d ₂ H7 Bore	b	d ₃	l ₁	l ₂	l ₃	r	Ø Handle GN 798	⚖
GN 324-125-*12-A	125	12	15	31	18	33	61.5	54	22	310
GN 324-125-*14-A	125	14	15	31	18	33	61.5	54	22	308
GN 324-140-*14-A	140	14	16.5	36	19	36	76.5	61	24	402
GN 324-140-*16-A	140	16	16.5	36	19	36	76.5	61	24	397
GN 324-160-*14-A	160	14	18	36	20	39	76.5	71	24	539
GN 324-160-*16-A	160	16	18	36	20	39	76.5	71	24	530
GN 324-200-*18-A	200	18	20.5	42	24	45	86.5	89	25	870
GN 324-200-*20-A	200	20	20.5	42	24	45	86.5	89	25	870
GN 324-250-*22-A	250	22	23	48	28	51	86.5	113	25	1490
GN 324-250-*26-A	250	26	23	48	28	51	86.5	113	25	1490

GN 324-R

Description	d ₁	d ₂ H7 Bore	b	d ₃	l ₁	l ₂	l ₃	r	Ø Handle GN 798	⚖
GN 324-125-*12-R	125	12	15	31	18	33	61.5	54	22	390
GN 324-125-*14-R	125	14	15	31	18	33	61.5	54	22	395
GN 324-140-*14-R	140	14	16.5	36	19	36	76.5	61	24	510
GN 324-140-*16-R	140	16	16.5	36	19	36	76.5	61	24	490
GN 324-160-*14-R	160	14	18	36	20	39	76.5	71	24	635
GN 324-160-*16-R	160	16	18	36	20	39	76.5	71	24	638
GN 324-200-*18-R	200	18	20.5	42	24	45	86.5	89	25	1036
GN 324-200-*20-R	200	20	20.5	42	24	45	86.5	89	25	1019
GN 324-250-*22-R	250	22	23	48	28	51	86.5	113	25	1628
GN 324-250-*26-R	250	26	23	48	28	51	86.5	113	25	1622

* Weight bore code B

* Weight bore code B