



* Дополните вариантом

 SW	 SR
RAL9005	RAL9006

GN 923.7-B

Описание	d1	d2 H7 Отверстие	b	d3	d4	h	l1	l2 ≈	l3 ≈	r	Ø Ручка	Рекомендуемая потайная шайба	⚖
GN 923.7-125-B12-R-*	125	12	24.5	23	31	4	18	45	60.5	44.5	22	GN 184-22	450
GN 923.7-125-B14-R-*	125	14	24.5	23	31	4	18	45	60.5	44.5	22	GN 184-22	440
GN 923.7-140-B14-R-*	140	14	26	23	36	4	19	47	75.5	52	24	GN 184-22	578
GN 923.7-140-B16-R-*	140	16	26	23	36	4	19	47	75.5	52	24	GN 184-22	580
GN 923.7-160-B14-R-*	160	14	26	23	36	4	20	48	75.5	61	24	GN 184-22	756
GN 923.7-160-B16-R-*	160	16	26	23	36	4	20	48	75.5	61	24	GN 184-22	750
GN 923.7-200-B18-R-*	200	18	27	23	42	4	24	53	85.5	80.5	25	GN 184-22	1080
GN 923.7-200-B20-R-*	200	20	27	23	42	4	24	53	85.5	80.5	25	GN 184-22	1050

GN 923.7-K

Описание	d1	d2 H7 Отверстие	b	d3	d4	h	l1	l2 ≈	l3 ≈	r	Ø Ручка	Рекомендуемая потайная шайба	⚖
GN 923.7-125-K12-R-*	125	12	24.5	23	31	4	18	45	60.5	44.5	22	GN 184-22	435
GN 923.7-125-K14-R-*	125	14	24.5	23	31	4	18	45	60.5	44.5	22	GN 184-22	440
GN 923.7-140-K14-R-*	140	14	26	23	36	4	19	47	75.5	52	24	GN 184-22	578
GN 923.7-140-K16-R-*	140	16	26	23	36	4	19	47	75.5	52	24	GN 184-22	583
GN 923.7-160-K14-R-*	160	14	26	23	36	4	20	48	75.5	61	24	GN 184-22	780
GN 923.7-160-K16-R-*	160	16	26	23	36	4	20	48	75.5	61	24	GN 184-22	760
GN 923.7-200-K18-R-*	200	18	27	23	42	4	24	53	85.5	80.5	25	GN 184-22	1070
GN 923.7-200-K20-R-*	200	20	27	23	42	4	24	53	85.5	80.5	25	GN 184-22	1060

Вес SW

