

This ISO Standard represents the basic for a system of nominal dimensions and sizes whereby the table mirrors the calculated values of basic tolerances relating to basic dimensions.

The use of this table is limited to smooth circular cylindrical workpieces or such with two parallel fitting planes or contact areas.

The values attributed to an ISO tolerance grade (IT) specify the tolerance value and hence the tolerance area. With ascending numbers, the size of the tolerance increases.

For identification purpose of the position of the tolerance area in relation to the nominal dimension (zero), the number chosen as tolerance grade IT is preceded by a letter.

Tolerance area H is the most common value for bores. It specifies that the minimum dimension of the bore corresponds to the nominal dimension.

The permissible maximum dimension corresponds to the nominal dimension plus the IT tolerance.

Examples:

bore 20 H7 = 20 +0.021/0 bore 8 H11 = 8 +0.090/0
 min. dimens.: 20.000 min. dimens.: 8.000
 max. dimens.: 20.021 min. dimens.: 8.090

ISO-Fundamental tolerance series DIN ISO 286

Tol. (µm)	Nominal sizes																									
	Grades	<3	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400												
IT	...	3	...	6	...	10	...	18	...	30	...	50	...	80	...	120	...	180	...	250	...	315	...	400	...	500
01	0.3	0.4	0.4	0.5	0.6	0.6	0.8	1	1.2	1.5	2	2.5	3	4	5	7	8	9	10	12	14	16	18	20	27	36
0	0.5	0.6	0.6	0.8	1	1	1.2	1.5	2	3	4	5	6	8	10	12	13	15	18	22	28	36	45	56	70	88
1	0.8	1	1	1.2	1.5	1.5	2	2.5	3.5	4.5	6	8	10	12	14	16	18	20	25	32	40	50	63	80	100	
2	1.2	1.5	1.5	2	2.5	2.5	3	4	5	7	8	10	12	14	16	18	20	22	28	36	45	56	70	88	110	
3	2	2.5	2.5	3	4	4	5	6	8	10	12	14	16	18	20	22	25	28	36	45	56	70	88	110	140	
4	3	4	4	5	6	7	8	10	12	14	16	18	20	22	25	28	32	36	45	56	70	88	110	140	180	
5	4	5	6	8	9	11	13	15	18	20	23	25	27	30	32	36	40	45	56	70	88	110	140	180	220	
6	6	8	9	11	13	16	19	22	25	29	32	36	40	45	50	56	63	70	80	90	100	110	120	140	180	
7	10	12	15	18	21	25	30	35	40	46	52	57	63	70	78	88	97	110	120	130	140	150	160	180	220	
8	14	18	22	27	33	39	46	54	63	72	81	89	97	110	120	130	140	150	160	170	180	190	200	220	280	
9	25	30	36	43	52	62	74	87	100	115	130	140	155	170	180	190	200	210	220	230	240	250	260	280	360	
10	40	48	58	70	84	100	120	140	160	185	210	230	250	280	300	320	340	360	380	400	420	440	460	480	600	
11	60	75	90	110	130	160	190	220	250	290	320	360	400	460	500	560	600	660	700	760	800	860	900	1000	1200	
12	100	120	150	180	210	250	300	350	400	460	520	570	630	700	760	830	900	970	1000	1100	1200	1300	1400	1500	1800	
13	140	180	220	270	330	390	460	540	630	720	810	890	970	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2200	2800	
14	250	300	360	430	520	620	740	870	1000	1150	1300	1400	1550	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2800	3600	
15	400	480	580	700	840	1000	1200	1400	1600	1850	2100	2300	2500	2800	3000	3200	3400	3600	3800	4000	4200	4400	4600	5000	6000	
16	600	750	900	1100	1300	1600	1900	2200	2500	2900	3200	3600	4000	4600	5000	5600	6000	6600	7000	7600	8000	8600	9000	10000	12000	
17	1000	1200	1500	1800	2100	2500	3000	3500	4000	4600	5200	5700	6300	7000	7600	8300	9000	9700	10000	11000	12000	13000	14000	15000	18000	
18	1400	1800	2200	2700	3300	3900	4600	5400	6300	7200	8100	8900	9700	11000	12000	13000	14000	15000	16000	17000	18000	19000	20000	22000	28000	

Tol. (µm)	Nominal sizes										
	...	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250
classes for bore
D9	+45	+60	+76	+93	+117	+142	+174	+207	+245	+285	+330
D12	+120	+150	+190	+230	+275	+330	+400	+470	+545	+630	+720
E8	+28	+38	+47	+59	+73	+89	+106	+126	+148	+172	+200
G6	+8	+12	+14	+17	+20	+25	+29	+34	+39	+44	+50
G7	+2	+4	+5	+6	+7	+9	+10	+12	+14	+15	+17
H7	+10	+12	+15	+18	+21	+25	+30	+35	+40	+46	+52
H8	+14	+18	+22	+27	+33	+39	+46	+54	+63	+72	+80
H9	+25	+30	+36	+43	+52	+62	+74	+87	+100	+115	+130
H11	+60	+75	+90	+110	+130	+160	+190	+220	+250	+290	+330
H12	+100	+120	+150	+180	+210	+250	+300	+350	+400	+460	+520
H13	+140	+180	+220	+270	+330	+390	+460	+540	+630	+720	+800
H14	+250	+300	+360	+430	+520	+620	+740	+870	+1000	+1150	+1300
JS9	±12.5	±15	±18	±21.5	±26	±31	±37	±43.5	±50	±57.5	±66
N9	-4	0	0	0	0	0	0	0	0	0	0
P9	-29	-30	-36	-43	-52	-62	-74	-87	-100	-115	-130
	-6	-12	-15	-18	-22	-26	-32	-37	-43	-50	-57.5
	-31	-42	-51	-61	-74	-88	-106	-124	-143	-165	-190
for shaft											
f7	-6	-10	-13	-16	-20	-25	-30	-36	-43	-50	-57.5
h6	-16	-22	-28	-34	-41	-50	-60	-71	-83	-96	-110
h7	0	0	0	0	0	0	0	0	0	0	0
h7	-6	-8	-9	-11	-13	-16	-19	-22	-25	-29	-33
h8	0	0	0	0	0	0	0	0	0	0	0
h8	-10	-12	-15	-18	-21	-25	-30	-35	-40	-46	-52
h9	0	0	0	0	0	0	0	0	0	0	0
h9	-14	-18	-22	-27	-33	-39	-46	-54	-63	-72	-80
h11	0	0	0	0	0	0	0	0	0	0	0
h11	-25	-30	-36	-43	-52	-62	-74	-87	-100	-115	-130
h13	0	0	0	0	0	0	0	0	0	0	0
h13	-60	-75	-90	-110	-130	-160	-190	-220	-250	-290	-330
h14	0	0	0	0	0	0	0	0	0	0	0
h14	-250	-300	-360	-430	-520	-620	-740	-870	-1000	-1150	-1300
js14	±125	±150	±180	±215	±260	±310	±370	±435	±500	±575	±660
n6	+10	+16	+19	+23	+28	+33	+39	+45	+52	+60	+69
p6	+4	+8	+10	+12	+15	+17	+20	+23	+27	+31	+36
	+12	+20	+24	+29	+35	+42	+51	+59	+68	+79	+90
	+6	+12	+15	+18	+22	+26	+32	+37	+43	+50	+57.5